

43" Outdoor Kiosk



The MetroClick single and double sided outdoor kiosk units can also help enhance any outdoor space. Fully weatherproof with integrated heating and cooling systems, we manufacture kiosks that are built to withstand all types of environments and even the harshest weather extremes.

Additionally, our devices are built in stainless steel encasements with Gorilla Glass screens to negate any concerns about vandalism or theft. We've got you covered rain, the sun, snow or rowdy patrons for corporate events, shows, and real estate.

Features

- Integrated 4K Camera
- Dual-sided Screen
- 10-Point Multi Touch
- Vandal proof glass
- IP67 Rated
- Optically bonded

Product Details

Product name: 43" Touchscreen PC Kiosk
Article code / EAN number: FTK43J1900W4G64GCAP / 6920734042555

LCD Panel

IP Rated Front Panel: IP40
Screen diagonal (Inch/cm): 43/106.73
Display active screen size: 93.02x52.33
Aspect ratio: 16:9
Physical resolution: 1920x1080
Maximum showable resolution (TPCs: external): 1920x1200
Colours displayed: 16.7M
Brightness (cd/m²): 360
Contrast: 1400:1
Typical reaction time Tr/ Tf (ms): 6/8
Visual Angle horizontal/vertical (°): 178/178
Backlight / Backlight Lifetime (hours): LED / 50,000

Touch Panel

Touch Technology: Projected Capacitive 10-point Multitouch
Touch Connector: USB
Touch Panel Drivers: Windows; Linux; Mac; Android
Touch Life (Contacts): Unlimited
Surface Hardness: 7H

Operation/Mechanical

Operating Temperature (°C): -10 ~ +60
Humidity Range (RH): 10%-90%
Net weight (kg): 60
Gross weight (kg): 103
Housing material: Aluminum

Power

Power Indicator: Green LED
Power Supply: 100-240V ACDC active switching; 24V DC-Out
Working Power (V): 24
Power Consumption (W): 90
Stand-By Consumption (W): <0.5

Internal Connectors

1x SO-DIMM Slot, max. 8GB, DDR3L-1333 Single channel memory
1x 12V DC power connector (2-pin); 1x 4-pin SATA power

connector
2x S-ATA 3GB/s ports; 1x 5-pin LCD power connector
1x VGA pin header; 1x SIM-card-Header (connected to MiniPCIe); 1x LVDS connector
1x S/PDIF output pin header
1x Line-Out / Mic-In audio pin header
1x 4-pin (2x2W) audio amplifier connector
1x PS/2 keyboard/mouse connector (6-pin)
1x USB 2.0 header supports additional 4x USB 2.0 ports
3x RS232/RS485 COM connectors, switchable between RS232/RS485 in BIOS
1x 8-bit Digital I/O interface
1x Chassis Fan connector

External Connectors

1x Display port
1x USB 3.0, 3x USB 2.0 ports
1x COM port Full-PIN (RS232/485; 5V/12V)
2x 10/100/1000Mbit RJ45 Ports
1x 24V DC-In
1x On/Off-button
1x 2.5" module slot, changeable SSD included

Expansion Slots

2x Mini Card slots with PCIe and USB interface (2x Full Height/Half height changeable)
1x PCIeX1 Straddle connector

Included Accessories

Power Supply (see Power section)
Driver DVD
Short Installation Manual
Stable Base

t