



239 West 29th Street
Ground Floor
New York City, NY 10001

646-843-0888
sales@metroclick.com



All-In-One Interactive Whiteboard

Available in the following sizes: 55", 65", 75" 86", 100"


Features

- **20 Point Touch Functionality** - Infrared Touch recognition can be used with a finger, included pen or other optional accessories
- **Simple & Easy Installation** - Standard VESA Mounting Pattern for mounting on a stand or wall mounting
- **High Resolution** - 4K Resolution with Wide Color Gamut, up to 1.07B Colors
- **Easy Video Conferencing** - Optional 12 Megapixel Camera and 6 Microphone Array make video calls and remote work easy
- **Powerful Android 11** - Amlogic A311D Embedded Mainboard with 4Gb RAM, 32GB SSD and Dual Wifi 6 Antennas



Features

- **Tough Rugged Designs** -Optically Bonded 3.2mm cover glass with Industrial LED Backlight Tested for 100k Hour Life
- **Versatile IO** - Dual HDMI Inputs, Display Port, USB-C and VGA make it easy to connect any existing device or accessory
- **Built for 24/7 Operation** - LED backlight tested to last more than 100k hours of non-stop operation
- **High Quality Optical Bonding** -Provides the sharpest most vivid display image in the industry
- **Slim & Lightweight Design** - Simple, sleek, and light frame designs are easy to mount anywhere
- **Fully Customizable for any Installations** - Case, connectors, peripherals etc.



86" Interactive Digital Whiteboard

Product name

Article code FT86OBHB02

86" Interactive Digital Whiteboard (4K)

IP Rating IP40

LCD Panel

Screen diagonal (Inch/cm) 86/218.44

Display active screen size (cm) 189.50×106.59

Aspect ratio 16:9

Display orientation Horizontal

Physical resolution 3840×2160

Maximum showable resolution 3840×2160

Colours displayed 10-bit(D), 1.07B

Brightness (cd/m²) 450

Contrast 1200 :1

Typical reaction time Tr/ Tf (ms) 8/8

Visual angle horizontal/vertical (°) 178/178

Backlight / backlight lifetime (hours) D-LED / min. 30,000

Light type Low-blue light

Operation / Mechanical

Storage Temperature (°C) -20 ~ +60

Humidity Range (RH) 20% - 90%

Net weight (kg) 64.00

Gross weight (kg) 75.00 (incl. cartonage)

Housing (mm) L × W × H 1963.5 × 1182.5 × 123.4

Mounting VESA 600 × 600

Operating Temperature (°C) 0 ~ +50

Package (mm) L × W × H 2044.0 × 1283.0 × 174.0

Housing material Aluminum

Installation Method (optional) Wall-mounted / Floor Stand

External Connectors

Front interface

1x HDMI-IN 2.0

2x USB 3.0 (public Type-A)

1x Type-C (60W+4K60+USB 2.0)

1x HDMI-OUT

Back interface

2x HDMI-IN

1x DP-IN

1x VGA-IN

1x Coax

2x USB 3.0

1x USB 2.0

2x USB Touch-OUT (3.0)

1x RS232

2x RJ45

1x PC Audio-IN

1x Line-OUT

1x Type-C (60W+4K60+USB 2.0)

PC System

CPU Amlogic A311D2 - 4× Cortex-A73 +

4× Cortex-A53 | 2.0/2.2GHz

Chipset A311D2

Graphic GPU Arm Mali-G52 MP8 | 800MHz

RAM / Memory 8GB

Storage 64GB eMMC

Network 10M/100M/1000M

Wireless module 2.4G+5G module

OS Android 11 (Android 13 available in June 2023)

Audio

Speaker position Bottom front

Speaker rated impedance 6Ω

Speaker freq. response F0 ~ 20 kHz ± 20%

Speaker max. power output 20W×2

Transmission range 5-8m

Touch Panel / Cover Glass

Touch sensor Infrared touch technology

Touch points 20-points touch

Touchscreen writing tools Finger, pen or other opaque objects

Touch resolution 32768×32768

Touch height 2-3mm

Touch response time (single-point) ≥8ms

Cursor speed 140 points/second

Positioning accuracy ± 1mm

Communication interface Dual USB

Cover glass thickness 3.2mm

Cover glass bonding Optical Bonding (in-house)

Touch surface hardness 7H

Surface treatment Anti-glare (chemical etching)

Glass strengthening Tempered

Transparency >88%

Haze 2~3%

Power

Working Power (V) AC 100-240V~50/60Hz

Power Consumption (W) ≤450

Stand-By Consumption (W) <0.5

Camera + Microphone

Camera Built-in 13 million pixels

Camera + Microphone

Camera Built-in 13 million pixels

Microphone 8-array microphone

Included in the Delivery

Power Cable

HDMI Cable

USB-Touch Cable